

VANDAL SERIES PROFESSIONAL TOURING LOUDSPEAKER SYSTEMS

Overview

The VANDAL Series is a premium professional sound reinforcement platform developed for touring, live events, worship centers, rental companies, festivals, and permanent installations. Built around high-power ferrite transducers, 4-inch voice coil compression drivers, and robust birch plywood enclosures, the series delivers exceptional output, reliability, and coverage for demanding professional applications.

V-SERIES LINE ARRAYS

VANDAL V10

Single 10-Inch Line Array Module

Specifications

- Configuration: 1 × 10" LF + 1 × 4" HF
 - LF Voice Coil: 100 mm (4")
 - Nominal Impedance: 16 Ω
 - Continuous Power: 500 W
 - Program Power: 1000 W
 - Peak Power: 2000 W
 - Sensitivity: 99 dB
 - Maximum SPL: 132 dB Peak
 - Frequency Response: 65 Hz – 18 kHz
 - Coverage: 100° × 10°
 - Enclosure: Birch Plywood
 - Finish: Touring Grade Polyurea
-

VANDAL V12

Single 12-Inch Line Array Module

Specifications

- Configuration: 1 × 12" LF + 1 × 4" HF
 - LF Voice Coil: 100 mm (4")
 - Nominal Impedance: 16 Ω
 - Continuous Power: 600 W
 - Program Power: 1200 W
 - Peak Power: 2400 W
 - Sensitivity: 100 dB
 - Maximum SPL: 134 dB Peak
 - Frequency Response: 60 Hz – 18 kHz
 - Coverage: 100° × 10°
 - Enclosure: Birch Plywood
 - Finish: Touring Grade Polyurea
-

VANDAL V210

Dual 10-Inch Line Array Module

Specifications

- Configuration: 2 × 10" LF + 2 × 4" HF
 - LF Voice Coil: 100 mm (4") Each
 - Nominal Impedance: 16 Ω
 - Continuous Power: 1000 W
 - Program Power: 2000 W
 - Peak Power: 4000 W
 - Sensitivity: 104 dB
 - Maximum SPL: 138 dB Peak
 - Frequency Response: 60 Hz – 18 kHz
 - Coverage: 100° × 10°
-

VANDAL V212

Dual 12-Inch Line Array Module

Specifications

- Configuration: 2 × 12" LF + 2 × 4" HF
 - LF Voice Coil: 100 mm (4") Each
 - Nominal Impedance: 16 Ω
 - Continuous Power: 1200 W
 - Program Power: 2400 W
 - Peak Power: 4800 W
 - Sensitivity: 105 dB
 - Maximum SPL: 140 dB Peak
 - Frequency Response: 55 Hz – 18 kHz
 - Coverage: 100° × 10°
-

S-SERIES SUBWOOFERS

VANDAL VS118

Single 18-Inch Touring Subwoofer

Specifications

- Configuration: 1 × 18" LF
 - Voice Coil: 100 mm (4")
 - Nominal Impedance: 8 Ω
 - Continuous Power: 1500 W
 - Program Power: 3000 W
 - Peak Power: 6000 W
 - Sensitivity: 99 dB
 - Maximum SPL: 137 dB Peak
 - Frequency Response: 35 Hz – 150 Hz
 - Enclosure Type: Bass Reflex
-

VANDAL VS218

Dual 18-Inch Touring Subwoofer

Specifications

- Configuration: 2 × 18" LF
- Voice Coil: 100 mm (4") Each

- Nominal Impedance: 4 Ω
 - Continuous Power: 3000 W
 - Program Power: 6000 W
 - Peak Power: 12000 W
 - Sensitivity: 105 dB
 - Maximum SPL: 144 dB Peak
 - Frequency Response: 30 Hz – 150 Hz
 - Enclosure Type: Bass Reflex
-

M-SERIES MONITORS

VANDAL VC12

12-Inch Coaxial Stage Monitor

Specifications

- Configuration: 12" Coaxial + 4" HF
 - LF Voice Coil: 100 mm (4")
 - Impedance: 8 Ω
 - Continuous Power: 600 W
 - Program Power: 1200 W
 - Peak Power: 2400 W
 - Sensitivity: 99 dB
 - Maximum SPL: 133 dB Peak
 - Coverage: 80° Conical
 - Frequency Response: 55 Hz – 18 kHz
-

VANDAL VC15

15-Inch Coaxial Stage Monitor

Specifications

- Configuration: 15" Coaxial + 4" HF
- LF Voice Coil: 100 mm (4")
- Impedance: 8 Ω
- Continuous Power: 500 W

- Program Power: 1000 W
 - Peak Power: 2000 W
 - Sensitivity: 100 dB
 - Maximum SPL: 134 dB Peak
 - Coverage: 80° Conical
 - Frequency Response: 50 Hz – 18 kHz
-

VANDAL VF210

Dual 10-Inch Floor Monitor

Specifications

- Configuration: 2 × 10" LF + 1 × 4" HF
 - LF Voice Coil: 100 mm (4") Each
 - Impedance: 8 Ω
 - Continuous Power: 1000 W
 - Program Power: 2000 W
 - Peak Power: 4000 W
 - Sensitivity: 103 dB
 - Maximum SPL: 137 dB Peak
 - Coverage: 80° × 50°
 - Frequency Response: 55 Hz – 18 kHz
-

Design Features

- Premium Birch Plywood Construction
 - Touring Grade Polyurea Finish
 - High-Power Ferrite Magnet Transducers
 - 100 mm (4") Voice Coil LF Drivers
 - 4" Compression Driver Technology
 - CNC Precision Manufacturing
 - Optimized FIR and DSP Compatibility
 - Heavy-Duty Rigging Hardware
 - Professional Touring Connectors
 - Designed for Large-Scale Sound Reinforcement
-

Applications

- Concert Touring
- Outdoor Festivals
- Houses of Worship
- Corporate Events
- Rental Companies
- Auditoriums
- Sports Facilities
- Theatres
- Permanent Installations

VANDAL Series™ Engineered for Impact. Built for the Road. Developed by Megawatts Audio.